




### Product Size



### Specification

<b>Model No.:</b>	RS-PAR56-20W(88126)
<b>Front cover &amp; Housing:</b>	Stainless steel 304+PC cover
<b>Dimensions:</b>	D295*H62mm
<b>Tempered Glass:</b>	PC cover
<b>LED chip:</b>	SMD 5050 Epistar
<b>LED Q'ty:</b>	105pcs *0.2W
<b>Cable gland:</b>	/
<b>Driver:</b>	Constant current driver
<b>Lens:</b>	120° bead PC cover
<b>Beam Angle Options:</b>	120°
<b>Power Cable:</b>	2*1.0mm <sup>2</sup> PVC cable / 4*0.75mm <sup>2</sup> / 2*1.0mm <sup>2</sup> +3*0.75mm <sup>2</sup> VDE rubber cable
<b>Protection Class:</b>	IP68
<b>Environment:</b>	Pool
<b>Mounting Hardware:</b>	Pool wall mounting
<b>Net Weight:</b>	1.8kgs with 1.8m cable
<b>Lifetime:</b>	>50000H

### Order information

Item code	Color	Light source(w)	Line Way	Input Voltage (v)	Operating current (mA)	Consumption (w)	Luminous (lm)
88126.105.01	2700-3000K	105*0.2	V+/V-	DC12-24	1666 / 833	20	1600
88126.105.02	4000-4500K	105*0.2	V+/V-	DC12-24	1666 / 833	20	1700
88126.105.03	5000-5500K	105*0.2	V+/V-	DC12-24	1666 / 833	20	1800
88126.105.04	6000-6500K	105*0.2	V+/V-	DC12-24	1666 / 833	20	1900
88126.105.05	Red	105*0.2	V+/V-	DC12-24	1666 / 833	20	400
88126.105.06	Green	105*0.2	V+/V-	DC12-24	1666 / 833	20	800
88126.105.07	Blue	105*0.2	V+/V-	DC12-24	1666 / 833	20	500
88126.105.08	Yellow	105*0.2	V+/V-	DC12-24	1666 / 833	20	1400
88126.105.09	RGB-DMX512 (3 channel)	105*0.2	V+/V- /D+/D-/GND	DC12-24	R: 500 / 250 B: 583 / 291	R: 6 B: 7	R: 120 B: 175
88126.105.10	Auto changing color	105*0.2	V+/V-	AC24	R: 250 B: 291	R: 6 B: 7	R: 120 B: 175
88126.105.11	RF remote control	105*0.2	V+/V-	DC12-24	R: 500 / 250 B: 583 / 291	R: 6 B: 7	R: 120 B: 175
88126.105.12	RGBV+ (build-in CC driver)	105*0.2	R/G/B/V+	DC12-24	R: 500 / 250 B: 583 / 291	R: 6 B: 7	R: 120 B: 175

