



Specification

| | |
|-----------------------------------|--|
| Model No.: | RS-RP36W316X(88254) / RS-RP48W316X(88254) |
| Front cover & Housing: | 316L Stainless steel lamp body+Stainless steel 304 Niche |
| Dimensions: | D180*H150mm |
| Tempered Glass: | 8mm thickness |
| LED chip: | CREE / EDISON |
| LED Q'ty: | 12pcs 3W LED / 12pcs 3in1 LED / 12pcs 4in1 LED |
| Cable gland: | Stainless steel 316L PG13.5 |
| Driver: | Constant current driver |
| Lens: | Clear, Bead, Frosted |
| Beam Angle Options: | 10° 30° 45° 60° 90° |
| Power Cable: | AWG 5/18 or AWG 3/18 SOW rubber cable |
| Protection Class: | IP68 |
| Environment: | Dry / Pool |
| Mounting Hardware: | Embedded System |
| Net Weight: | 5.5kgs with 1.5m cable |
| Lifetime: | >50000H |

Order information

| Item code | Color | Light source(w) | Line Way | Input Voltage (v) | Operating current (mA) | Consumption (w) | Luminous (lm) |
|--------------|----------------------------|-----------------|---------------------|-------------------|-----------------------------------|-------------------------------|------------------------------------|
| 88254.123.01 | 2700-3000K | 12*3 | V+/V- | AC/DC12-24 | 1500 | 36 | 1680 |
| 88254.123.02 | 4000-4500K | 12*3 | V+/V- | AC/DC12-24 | 1500 | 36 | 1776 |
| 88254.123.03 | 5000-5500K | 12*3 | V+/V- | AC/DC12-24 | 1500 | 36 | 1860 |
| 88254.123.04 | 6000-6500K | 12*3 | V+/V- | AC/DC12-24 | 1500 | 36 | 1860 |
| 88254.123.05 | Red | 12*3 | V+/V- | AC/DC12-24 | 1000 | 24 | 420 |
| 88254.123.06 | Green | 12*3 | V+/V- | AC/DC12-24 | 1500 | 36 | 1080 |
| 88254.123.07 | Blue | 12*3 | V+/V- | AC/DC12-24 | 1500 | 36 | 480 |
| 88254.123.08 | Yellow | 12*3 | V+/V- | AC/DC12-24 | 1500 | 36 | 1140 |
| 88254.123.09 | RGB-DMX512 (3 channel) | 12*3 | V+ /V- /D+ /D- /GND | DC24 | R: 333 B: 500 G: 500 | R: 8 B: 12 G: 12 | R: 140 B: 160 G: 360 |
| 88254.123.10 | RGB-DMX512 (3 channel) | 12*3in1 | V+ /V- /D+ /D- /GND | DC24 | R: 500 B: 500 G: 500 | R: 12 B: 12 G: 12 | R: 300 B: 360 G: 720 |
| 88254.123.11 | Auto changing color | 12*3 | V+/V- | AC24 | R: 333 B: 500 G: 500 | R: 8 B: 12 G: 12 | R: 140 B: 160 G: 360 |
| 88254.123.13 | RGBV+ (build-in CC driver) | 12*3 | R/G/B/V+ | DC24 | R: 333 B: 500 G: 500 | R: 8 B: 12 G: 12 | R: 140 B: 160 G: 360 |
| 88254.124.14 | RGBW-DMX512 (4 channel) | 12*4in1 | V+ /V- /D+ /D- /GND | DC24 | R: 500 B: 500 G: 500 W: 500 | R: 12 B: 12 G: 12 W: 12 | R: 300 B: 360 G: 720 W: 1080 |

