



Specification

Model No.:	RS-UG6W-PM(88229)
Front cover & Housing:	304 Stainless steel+Aluminum body+Plastic installation box
Dimensions:	D145*H90mm
Tempered Glass:	8mm thickness
LED chip:	Cree / Epistar
LED Q'ty:	6pcs 1W LED
Cable gland:	Nickel plated brass PG9
Driver:	Constant current driver
Lens:	Clear, Bead, Frosted
Beam Angle Options:	10° 30° 45° 60° 90°
Power Cable:	2*1.0mm ² / 3*0.75mm ² / 4*0.75mm ² / 2*1.0mm ² +3*0.75mm ² VDE rubber cable
Protection Class:	IP67
Environment:	Dry
Mounting Hardware:	Embedded System
Net Weight:	1.2kgs with 1m cable
Lifetime:	>50000H

Order information

Item code	Color	Light source(w)	Line Way	Input Voltage (v)	Operating current (mA)	Consumption (w)	Luminous (lm)
88229.061.01	2700-3000K	6*1	V+/V- or L/N/G	AC/DC12-24, AC90-230	500 / 250 / 27-54	6	540
88229.061.02	4000-4500K	6*1	V+/V- or L/N/G	AC/DC12-24, AC90-230	500 / 250 / 27-54	6	570
88229.061.03	5000-5500K	6*1	V+/V- or L/N/G	AC/DC12-24, AC90-230	500 / 250 / 27-54	6	600
88229.061.04	6000-6500K	6*1	V+/V- or L/N/G	AC/DC12-24, AC90-230	500 / 250 / 27-54	6	600
88229.061.05	Red	6*1	V+/V- or L/N/G	AC/DC12-24, AC90-230	500 / 250 / 27-54	6	150
88229.061.06	Green	6*1	V+/V- or L/N/G	AC/DC12-24, AC90-230	500 / 250 / 27-54	6	360
88229.061.07	Blue	6*1	V+/V- or L/N/G	AC/DC12-24, AC90-230	500 / 250 / 27-54	6	180
88229.061.08	Yellow	6*1	V+/V- or L/N/G	AC/DC12-24, AC90-230	500 / 250 / 27-54	6	420
88229.061.09	RGB-DMX512 (3 channel)	6*1	V+/V- /D+/D-/GND	AC/DC12-24	R: 166 / 83 B: 166 / 83 G: 166 / 83	R: 2 B: 2 G: 2	R: 50 B: 60 G: 120
88229.061.10	Auto changing color	6*1	V+/V-	AC12-24	R: 166 / 83 B: 166 / 83 G: 166 / 83	R: 2 B: 2 G: 2	R: 50 B: 60 G: 120
88229.061.12	RGBV+ (build-in CC driver)	6*1	R/G/B/V+	DC12-24	R: 166 / 83 B: 166 / 83 G: 166 / 83	R: 2 B: 2 G: 2	R: 50 B: 60 G: 120

