




Product Size



Specification

Model No.:	RS-FT108W316X(88156) / RS-FT120W316X(88156) / RS-FT144W316X(88156)
Front cover & Housing:	Stainless steel 316L
Dimensions:	D255*H46mm (Nozzle hole size: 80mm)
Tempered Glass:	10mm thickness
LED chip:	Cree / Edison / Epistar
LED Q'ty:	36pcs 3W LED / 36pcs 3in1 LED / 96pcs 3W LED / 36pcs 4in1 LED
Cable gland:	Stainless steel 316L PG13.5
Driver:	Constant current driver
Lens:	Clear, Bead, Frosted
Beam Angle Options:	10° 20° 30° 45° 60° 90°
Power Cable:	AWG 5/18 or AWG 3/18 SOW rubber cable
Protection Class:	IP68
Environment:	Dry / Submerged
Mounting Hardware:	Surface Mounted System / Nozzle fixed
Net Weight:	7.5kgs with 1.5m cable
Lifetime:	>50000H

Order information

Item code	Color	Light source(w)	Line Way	Input Voltage (v)	Operating current (mA)	Consumption (w)	Luminous (lm)
88156.363.01	2700-3000K	36*3	V+/V-	DC24	4500	108	5040
88156.363.02	4000-4500K	36*3	V+/V-	DC24	4500	108	5220
88156.363.03	5000-5500K	36*3	V+/V-	DC24	4500	108	5580
88156.363.04	6000-6500K	36*3	V+/V-	DC24	4500	108	5580
88156.363.05	Red	36*3	V+/V-	DC24	3000	72	1260
88156.363.06	Green	36*3	V+/V-	DC24	4500	108	3240
88156.363.07	Blue	36*3	V+/V-	DC24	4500	108	1440
88156.363.08	Yellow	36*3	V+/V-	DC24	4500	108	3420
88156.363.09	RGB-DMX512 [3 channel]	36*3	V+/V- /D+/D-/GND	DC24	R: 1000 B: 1500	R: 24 B: 36	G: 36 G: 1080 B: 480
88156.363.12	RGBV+ [build-in CC driver]	36*3	R/G/B/V+	DC24	R: 1000 B: 1500	R: 24 B: 36	G: 36 G: 1080 B: 480
88156.363.13	RGB-DMX512 [3 channel]	36*3in1	V+/V- /D+/D-/GND	DC24	R: 1500 B: 1500	R: 36 B: 36	G: 36 G: 2160 B: 1080
88156.364.14	RGBW-DMX512 [4 channel]	36*4in1	V+/V- /D+/D-/GND	DC24	R: 1500 B: 1500 W: 1500	R: 36 B: 36 W: 36	G: 36 G: 2160 B: 1080 W: 3240
88156.963.16	RGBW-DMX512 [4 channel]	96*3	V+/V- /D+/D-/GND	DC24	R: 1250 B: 1250	R: 30 B: 30 W: 30	G: 360 G: 1380 B: 860 W: 1900

